





2.7


LED SECURE



+ Brida
Clamp
Collier



APLICACIONES INDICADAS / SUITABLE APPLICATIONS / APPLICATIONS APPROPRIÉES



IT - DE



RG1

MACADAM

3/4

UGR
<19

CR>80

L70B50
>
50.000


IP68-2
IK10

CE
EN 60598-1

2014/34/UE



II 3GD
Ex nR II C T6 Gc
Ex tb IIIC T85°C Dc



Ref.	Potencia Power Puissance (W)	Emisión bruta Gross output Flux de la source (Lm)	Emisión neta Net output Flux sortant (Lm)	Tª color Tª colour Tª couleur (°K)	L (mm)	D (mm)	D + brida D + clamp D + fixation (mm)	Embalaje Packaging Emballage
LS114	13	1550	1037	4000	727	83	133	1
LS114U	13	1900	1271	4000	727	83	133	1
LS124	16	2670	1786	4000	727	83	133	1
LS124U	21	3380	2261	4000	727	83	133	1
LS214	24	3200	2140	4000	1337	83	133	1
LS214U	26	3800	2542	4000	1337	83	133	1
LS224	32	5340	3571	4000	1337	83	133	1
LS224U	42	6760	4522	4000	1337	83	133	1
LS314	29	4000	2675	4000	1637	83	133	1
LS314U	32	4750	3177	4000	1637	83	133	1
LS324	40	6700	4481	4000	1637	83	133	1
LS324U	46	7000	4683	4000	1637	83	133	1

REF. + U = TENSIÓN DE ALIMENTACIÓN 110-277V/50-60HZ

ACCESORIOS LED SECURE / LED SECURE ACCESSORIES / ACCESSOIRES LED SECURE

LÍNEA CONTINUA
CONTINUOUS LINE CONNECTION
CÂBLAGE TRAVERSANT

3 polos / 3 poles / 3 pôles

5 polos / 5 poles / 5 pôles

1-10
DALI

EMERGENCY
1h / 3h